

## **Technical information**

Carton of 12 x 1 | bottles 5 | canister 10 | canister

order No. 00261 order No. 30251 order No. 30250

Pore-deep removal of dirt

#### before





All information contained in our brochures is accurate to the best of our knowledge and experience. No liability can be derived from the information herein. For details about the product, please refer to the safety data sheet. 

30 0918



# Pore-deep maintenance and basic cleaner for fine stoneware and ceramic flooring

# Area of application

FOREX is suitable for all waterproof and alkali-resistant floorings, particularly ceramic tiles and alkali-resistant stone floors. For manual and mechanical cleaning.









# **Application**

Mechanical basic cleaning

Dilute 10–15 % FOREX with cold, fresh water (1 part FOREX to 9 parts water). Pre-rinse floor including grouting with plenty of cold, fresh water. Apply plenty of cleaning solution to the floor (500–650 ml application solution/m²). Exposure time approx. 5 minutes. During the exposure time, manually or mechanically keep moving the dirt. After the exposure time has passed, completely go over the flooring using a single-disc machine and suitable pad/brush, thoroughly vacuuming the treated floor. Thoroughly mop the floor (multiple times if required) with fresh water and vacuum. Remove loosened residue from the floor by wiping with fresh water – if required, wash the flooring and go over with a water extractor.

Maintenance cleaning

Apply 0.25-5.0% of FOREX application solution. Clean manually or using a scrubbing machine in a 2-stage wet wiping method.

### **Product characteristics**

- RK-listed
- Removes stubborn dirt after a short exposure time
- For daily maintenance cleaning and basic cleaning
- Particularly suitable for rough and microporous stoneware tiles
- Low-foaming

#### Note

Test material compatibility on an inconspicuous area prior to use. Risk of slipping! Thoroughly pre-soak grouting with cold, fresh water.

pH conc 0 2 4 6 8 10 12

