

Kiehl-Parketta

Superior-quality liquid hard wax

Features

Superior-quality solvent-based wax: prevents swelling of water-sensitive floors. Easy to handle, offers excellent penetration and high diffusion properties, and is wipe-proof. Treated floors are water-repellent and should preferably be cleaned with damp mopping. The product must not be mixed with water! Do not pour the product into sewer.

Ingredients

Hard waxes, water-insoluble solvents, fragrances.

Application

Suitable for the maintenance of all European types of wood. With untreated exotic woods, please always test a small inconspicuous spot before use. For interior use on untreated as well as on waxed, oil-waxed and sealed-waxed wood surfaces, such as parquet, planks, paving, industrial parquet, stairs, OSB boards, glued laminated timber, etc.

Directions

The temperature of the floor and of the product needs to be between 15°C and 25°C. Rooms have to be well ventilated while and after working; do not smoke. Remove loose dirt with damp cloths. Shake well before use!

Waxing and subsequent waxing:

Suitable for use on untreated, clean and dust-free professionally-sanded wooden floors (or repaired with wood cement and fine-sanded - grain size 100-200). Also suitable for clean and dust-free floors which have already been waxed with Kiehl-Parketta. Apply approx. 250 ml on the floor and immediately distribute on about 5 square metres in a thin layer and overlapping paths, using a waxer or a flat mop. Depending on the surface structure, 1-3 layers at approx. 60-minute intervals are necessary.

Spray buffing method with explosion-proof machine:

Already waxed surfaces: Fill spray can with a 1:1 dilution of Kiehl-Parketta and Kiehl-Wax-Ex. Spray sparingly onto dirt stains or scuff marks and immediately buff to a shine. Turn dirty red pad or replace with a clean one.

Polishing:

Polish the dry, mat wax film with a polishing machine (150-1,000 r.p.m., brush or pad) until shine appears.

Use Kiehl-Wax-Ex to clean working tools.

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product.



Maintenance
and cleaning
of wood /
parquet

Coverage per square metre

Waxing: 80-150 ml depending on the absorbency of the wood.

Subsequent waxing: 20-40 ml

Spray buffing method: 3-5 ml

GHS 02, 07, 08, Danger (in concentrated form);

H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.

P271 Use only outdoors or in a well-ventilated area. P301+P330+P331 IF

SWALLOWED: Rinse mouth. Do NOT induce vomiting. P370+P378 In case of fire: Use extinguishing powder to extinguish. EUH066 Repeated exposure may cause skin dryness or cracking.

Contains C10-12 Alkane/Cycloalkane (INCI).

No consumer product according to 1999/44/EC Art. 1! For professional use only!

Packaging

Carton of 2 x 5 litre metal containers

Art. No. j 22 01 70

Viscosity depends on temperature

