

Kiehl-Eco-Refresher

Water-based film-building wood oil

Features

New development, unique worldwide, patent filed.

Enhances the natural colour of the wood. Dries to a matt finish, contains no perfume or pigment, is oxidatively drying, diffusion-open, and can be polished. Easy to handle, film-building, high-filling capacity, tread-proof after 2 hours and wipe-proof after approx. 2 days. Fulfills the chemical requirement of the German Industrial Norm 71-3 (free of heavy metal). Solvent-free. Once the floor has completely hardened, you can treat it with Kiehl-Legnodor for further protection.

Ingredients

Vegetal oil components, waxes, nonionic surfactants < 5%, drying agents free of heavy metal. pH value (concentrate): approx. 8

Application

Suitable for the maintenance of all European types of wood. With untreated exotic woods, please always test a small inconspicuous spot before use. For the basic treatment and re-oiling of wooden surfaces, such as parquet, planks, paving, industrial parquet, UV-oiled parquet, stairs, OSB boards, glued laminated timber, etc. Not suitable for sealed, coated, or waxed wooden surfaces.

Directions

It is imperative that floors are clean, dry and free from polish, wax, silicone, dust, etc. and uncoated before Kiehl-Eco-Refresher is applied. The temperature of the floor needs to be between 10°C and 25°C. Shake well before use!

Basic treatment of untreated wooden floors: Detailed instructions are available on request.

Re-oiling: Wood surfaces subject to hard wear first have to be dry-cleaned mechanically (rotary floor machine, suction ring, vacuum unit, Kiehl-Legno-Pad). Move machine in spirals until the surface dirt has been dissolved and the floor is thoroughly clean, presenting an even appearance. Finally, remove any remaining sanding dust with damp cloths.

How to use it? Use undiluted. Apply 200 ml on the clean floor and immediately distribute on approx. 10 square metres in a thin layer and overlapping paths, using a waxer or a flat mop. Depending on the surface structure, 1-2 layers at approx. 2 hour intervals are necessary.

Polishing: Polishing the surface with a rotary floor machine (approx. 150-1,000 r.p.m.) and Multi-Disc within 24 hours after drying will solidify the oil layer and bring it to a shine. Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product.

Use water to clean work tools.

Note In case of contact with eyes, rinse immediately with plenty of water. Do not empty into drains, aquatic environment or earth. Avoid eating, drinking and smoking during the use of Kiehl-Eco-Refresher. Keep away from children! Open containers have to be used up rapidly. Dispose of dried product residues as normal waste. Dispose of liquid product residues at the local collection points. Immediately close the container after use. Based on natural raw materials. The packaging material can be recycled. For more information as to why this product has been awarded the Flower please visit the web-site: www.ecolabel.eu.



Maintenance and cleaning of wood / parquet

Coverage per square metre

Basic treatment: approx. 50 ml/m², depending on the absorbency of the wood

Re-oiling: approx. 20 ml/m², depending on the absorbency of the wood

No consumer product according to 1999/44/EC Art. 1!

For professional use only!

Packaging

Carton of 2 x 5 litre containers

Art. No. j 22 16 05

Protect from frost!

