

Sunglorin G 145

Self-gloss emulsion











Area of application

- For coatable and water-resistant floor coverings such as sealed parquet, linoleum, PVC and rubber
- Natural and artificial stone

Product properties

- Can be used as wiping care
- Easy removability
- Polishable with the single-disc machine
- Good dispersive capacity
- Slip-resistant according to DIN EN 16165
- Suitable for cleaning

Application and dosage

- Always use cold water.
- Requirement: Thoroughly cleaned, neutralised and dry floor covering.
- Floor covering must be free of surfactants.
- Apply undiluted a thin layer in 2 3 layers.
- Consumption: 25 35 ml / per m2 / per order



undiluted 1:1 with water



100 - 200 ml / 10 l water

Note

- Protect from frost.
- Before processing, turn off heat sources (underfloor heating, heating, hot supply air).
- Avoid direct sunlight.
- Changes or variations in colour of the product do not impact on the quality. The product image may differ in colour and shape from the original.
- Safety: Hazard statements and safety precautions can be found in the relevant safety data sheet, which is available at www.buzil.com.
- Storage: Always keep containers closed. Store at room temperature in the original container. Consume opened containers within 9 months.
- **Environmental:** Feed residual emptied containers to the dual system. For detailed information see environmental information.

Further information

Product colour: whiteGISBAU code: GE 10

■ UFI code: VA20-U0F9-Y00M-PXU4

• For professional use only.

Sales units

G145-0010RA: 1 x 10 | canisterG145-0001RA: 12 x 1 | bottle





