

Kiehl-Legnodur-brillant

Self-shining one-component long-term coating

Features

Plasticizer-free and non-metallised PU dispersion which dries like a lacquer. Thanks to the high solids content, the product forms a resistant and easy-to-clean protective coating. After dry cleaning, the surface can be recoated. The coating cannot be removed by wet stripping.

Ingredients

Polymer dispersions, polyethylene waxes, water-soluble solvents, preservatives (Methylisothiazolinone, Benzisothiazolinone).
pH value (concentrate): approx. 8

Application

For wooden surfaces which have been treated with wood oils (e. g. Kiehl-Eco-Refresher) or sealings. Is also suitable for resilient floor surfaces which can be coated. Not suitable for surfaces which have been treated with solvent wax.

Directions

Please test a small inconspicuous spot before first application.
Make sure the surfaces are clean, free from parting agents and properly prepared.

Preparation of the surface:

Parquet surfaces (oiled, sealed, already coated) have to be dry cleaned (Kiehl-Legno-Pad) before coating.
Accruing dust has to be removed.

New resilient floor coverings have to be cleaned intensively with Torvan Concentrate (100 ml in 8 litres of water) before coating.
Already coated resilient floor coverings have to be stripped, e. g. with Veroclean (3 litres in 8 litres of water). On resilient floor coverings which have already been treated with Kiehl-Legnodur it is necessary to carry out dry cleaning with a Kiehl-Legno-Pad.



Coating:

Apply approx. 300 ml on the floor undiluted and immediately distribute on about 10 square metres in a thin layer and overlapping paths, using a waxer or a flat mop. Continue working in overlapping paths (wet in wet). Depending on the surface structure, 1-2 layers at approx. 90-minute intervals are necessary. Only dry layers form a wear-resistant protective coating.

Use water to clean work tools.

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product.

Maintenance and cleaning of wood / parquet

Coverage per square metre

Coating: 30 ml per application



Keep out of the reach of children. Not suitable for paint spraying. Use P2 dust filter for grinding. When using do not eat, drink or smoke. In case of contact with eyes or skin, immediately and thoroughly rinse with water. Ensure good ventilation during use and drying. Clean utensils immediately after use with soap and water. Do not allow product to enter drains, waterways or soil. Make sure that containers are completely empty for recycling. Liquid paint leftovers should be returned to a collection facility for paint residues. Contains: 2-Methyl-2H-isothiazol-3-on, 1,2-Benzisothiazol-3(2H)-on. Information for allergy sufferers at +49-81 34 / 93 05-0.

No consumer product according to 1999/44/EC Art. 1! For professional use only!

Packaging

Carton of 2x5 litre containers

Art. No. j 22 07 05

Protect from frost!

