



Pore-deep decoater

Area of application

TEMPEX XTREME is suitable for all waterproof, alkali-sensitive hard wood floors. Powerful basic cleaner for stubborn, aged and refurbished maintenance film and impurities.



Application

Mechanical basic cleaning and decoating

Dilute TEMPEX XTREME in a ratio of 1:2 with cold, fresh water (1 part TEMPEX XTREME to 2 parts water). Remove large dirt particles from floor covering. Apply plenty of cleaning solution to the floor (500–650 ml application solution/m²). Exposure time approx. 10 minutes. After the exposure time has passed, completely go over the flooring using a single-disc machine and suitable pad/brush, thoroughly vacuuming the treated floor. Remove loosened residue from the floor by wiping with fresh water – if required, wash the flooring and go over with a water extractor.

Product characteristics

- Removes sticky, aged coating without leaving residue – independent of manufacturer
- Pore-deep decoater – streak-free
- Increased efficiency during exposure times of 20–30 minutes – i.e. ideal for application using column cleaning
- Fast, efficient dissolving capacity
- No neutralisation required
- High material compatibility

Note

For linoleum floors, an intermediate smoothing step is recommended after the basic clean. For older maintenance films, a complete, dry grinding of the maintenance film prior to applying the basic cleaning solution increases efficiency. Test material compatibility on an inconspicuous area prior to use. For older, open-pore or previously damaged floors, particularly linoleum floors, the deep-cleaning effect of TEMPEX XTREME is enhanced so that linseed oils and resins are transported to the surface. This visually evens out discolouration or saponification of the floor – this effect is levelled out while the floor dries out. Risk of slipping! Ensure a sufficient supply of fresh air during and after application – windows must be opened! Do not use in non-ventilated rooms! Deactivate ventilation equipment and ensure a fresh air supply! Ideally ensure room is supplied with plenty of fresh air prior to use.

Technical information

10 l canister

order No. 30871

Residue-free/pore-deep removal of sticky, aged coatings or coatings from maintenance films previously cleaned



All information contained in our brochures is accurate to the best of our knowledge and experience. No liability can be derived from the information herein. For details about the product, please refer to the safety data sheet. (GB) 0917

pH conc

0	2	4	6	8	12	14
---	---	---	---	---	----	----

DR.SCHNELL GmbH & Co. KGaA
Taunusstraße 19 · 80807 Munich
Tel. +49 89 3506080
info@dr-schnell.com
www.dr-schnell.com

Wir leben Hygiene
DR.SCHNELL
QUALITÄT UND SERVICE