

# **Technical information**

10 | canister

Order No. 30874

Removal of dirt, water-soluble and water-insoluble care films such as TOPCARE ECO  $\,$ 



### JW 1235

Awarded the Austrian Eco-label. Further information on this can be found at: www.umweltzeichen.at







All information contained in our brochures is accurate to the best of our knowledge and experience. No liability can be derived from the information herein. For details about the product, please refer to the safety data sheet. © 0218



# Environmentally friendly basic cleaner and decoater

# Area of application

TEMPEX ECO is suitable for all waterproof hard floor coverings, including alkali-sensitive ones. For thorough removal of wax and polymer dispersion films such as TOPCARE ECO. With the pH value of an all-purpose cleaner, TEMPEX ECO is also ideally suited to basic cleaning of linoleum and rubber flooring as well as cleaning durable natural and artificial stone floors. The special combination of active ingredients, and its good wetting properties, makes TEMPEX ECO furthermore an ideal choice for demanding cleaning work.

Its eco-friendly formulation made possible the awarding of an Austrian Eco-label.







#### **Application**

Mechanical basic cleaning and decoating:

Dilute TEMPEX ECO for classic decoating in a ratio of 1:3 – 1:4 (classic mechanical dirt removal in a ratio of 1:9 (10% solution)) with cold clear water (1 part TEMPEX ECO to 3 or 4 parts water (20-25%)). Rid floor covering of large dirt particles. Apply a generous amount of cleaning solution to the floor (500-650 ml application solution/m²). Exposure time approx. 10 minutes. Once the exposure time has finished, go over entire floor surface with a single disc machine and suitable pad disc/brush. Remove loosened residue from surface by mopping with fresh water – if necessary, rinse surface and sop up using a water-suction cleaner.

## **Product characteristics**

- Awarded the Austrian Eco-label
- Versatile cleaner
- Cleans and decoats
- Low-odour
- No rinsing or neutralisation required
- For use in double trolleys, automatic scrubbers and single disc machines

### Note

For aged care films, an all-over dry sanding of the care film prior to applying the basic cleaning solution increases efficiency. Before application, test compatibility of materials on an inconspicuous area. Danger of slipping! Ensure sufficient aeration and supply of fresh air during and after application! Ideally, concentrate on ensuring a fresh air supply once again prior to using the room. This product is intended for commercial use only. Keep out of the reach of children. Do not mix with other detergents.





pH conc 0 2 4 6 8 12 14

DR.SCHNELL GmbH & Co. KGaA

Taunusstraße 19 · 80807 Munich Tel. +49 89 3506080 info@dr-schnell.com www.dr-schnell.com

